



- NOTES: -
1. MAXIMUM NUMBER OF STEPS PER FLIGHT = 10
 2. MINIMUM NUMBER OF STEPS PER FLIGHT = 2
 3. HANDRAILING SHALL BE PROVIDED WHERE THERE ARE MORE THAN 4 RISERS IN ONE FLIGHT. PROVIDE ON ONE SIDE ONLY.
 4. HANDRAILING WILL BE HOT DIPPED GALVANISED AFTER FABRICATION IN ACCORDANCE WITH AS 1650-1981
 5. COMPRESSIVE STRENGTH OF CONCRETE (F_c) AT 28 DAYS TO BE 20MPa.
 6. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE SHOWN.
 7. WHERE SMALL BANKS OF STEPS ARE LOCATED IN ISOLATION ADVANCE WARNING SIGNS ARE TO BE PROVIDED.
 8. WHERE STEPS ARE TO LINK CYCLEWAYS PROVISIONS ARE TO BE MADE FOR WALKING CYCLES UP/DOWN ADJACENT TO THE STEPS IN ACCORDANCE WITH THE CURRENT AUSTRROADS STANDARDS. DETAILS TO BE SUBMITTED FOR APPROVAL.

SNOWY RIVER SHIRE COUNCIL

PATHWAY STEP DETAIL

Surveyed By	Drawn By	Scale	Approved By	Date	Datum	Sheet No	Ref. No	Plan No
Job No	Checked By	N.T.S.						SD24a
Disk No	Passed By							